

SRPT 30 150 : Technical Specifications

The new SRPT 30 incorporates the proven synthesizer and RF amplifier technology that has been proven in the SRPT 40A and the STL 20C. The features are similar to the RPT 30, but is wide band so there is no minimum separation of the two frequencies as long as they are within the band selected.

RF SPECIFICATIONS

Frequency Band:

135-185 MHz

Typical Max RF Output Power:

30 W

Selection:

Any two frequencies within selected band can be factory set with 5 and 6.25 kHz steps

Deviation:

Adjustable, ± 20 kHz max

Stability over Operating Temperature range:

$\pm 0.0001\%$

Agility and Accuracy:

For frequencies divisible by 5 kHz or 6.25 kHz:

$\pm 0.00004\%$

For MOST frequencies NOT divisible by 5 kHz or 6.25 kHz:

$\pm 0.00015\%$

AUDIO SPECIFICATIONS

Modulation Control:

Broadcast quality compressor/limiter built-in

Audio Input Level:**Mic In:**

-68 dB to -35 dB

Line In:

0 to +10 dBm, 8-600 Ohms

Mono Operation:**Frequency Response:****50 Hz to 3 kHz:**

± 1.5 dB, 1.5 kHz Dev

50 Hz to 7.5 kHz (Standard):

± 1.5 dB, 5 kHz Dev

50 Hz to 10.5 kHz:

± 1.5 dB, 7.5 kHz Dev

Signal To Noise:

≥ 53 dB, 5 kHz deviation, 75 μ sec pre/de-emphasis

Frequency Response:

± 1.5 dB from 50 Hz to audio bandwidth, 75 μ sec pre-emphasis

Distortion:

$\leq 2\%$ from 50 Hz to audio bandwidth, 75 μ sec pre-emphasis

Spurious Emission:

More than 60 dB below carrier

Encoding:

Sub-audible (27 Hz) tone encoder built in

RF Output Impedance:

50 Ohm

MECHANICAL/PHYSICAL

Audio Inputs:

4 balanced microphone (150 Ohm) inputs (XLR-3) with mixing controls, 1 input switchable to balanced line level at no. 4 input and D connector on rear

Accessory Connector:

15-pin D connector for DC power, remote control, encode, line level input

RF Connector:

Type N female

Dimensions (Unpacked):

3.5"H x 11.5"W x 14.3"D (8.9cm H x 29.2cm W x 36.8cm D)

Weight (Unpacked):

8.25 lbs (3.74 Kg)

ENVIRONMENTAL

Operating Temperature:

-10° C to +45° C

Altitude:

10,000 ft (3048m) max

Humidity:

95% maximum, non-condensing

ELECTRICAL

Approx PA Current Reading (at max power output):

6.5 A to 7.5 A

Power Requirements:

AC:

110-120 VAC or 220-240 VAC (manually switched internally on power supply), 50/60 Hz

External DC:

12-15 V to 15-30 V

Power Consumption:

300 W Max (150 W Typical)

Heat Dissipation:

300 W Max

Fuse:

2.5 A Slo-Blo for 115 VAC operation, 1.25 A Slo-Blo for 230 VAC operation